

INPUT

(Entrada)

- ACW (BLUE/BLACK)
- ACL (GREEN/BLACK)
- GRY (GREEN/YELLOW)
- WHT (WHITE)

MINI MADE IN CHINA
(IN 2016)

S/N: 
RCC89V3R15

INPUT

100-240V ~ 50/60Hz
277V ~ 50/60Hz
(277V - for North America only)

OUTPUT

Max. 25V rms
20V rms, 0.2A CC and CF loads (R, L or C)

Rated Power (R, L or C) (Passive Elements): 10W/20W

1, 50°C Input 100-240V ~ 277V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

1, 40°C Input 100-240V ~

(No. y) (No. de Modelo)

LEDH4-M-M

Convertidor para LED, uso interior y exterior

OUTPUT

(Salida)

- BLACK (Negro) Po
- RED (Rojo) V+



Ebene 2

