



|   |       |      |  |                |
|---|-------|------|--|----------------|
| without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)               | Depth | 85   | range 250 nm to 800 nm, at full-load                               |                |
| Claim of equivalent power <sup>(a)</sup>  |       | -    | If yes, equivalent power (W)                                       | -              |
|   |       |      | Chromaticity coordinates (x and y)                                 | 0,388<br>0,385 |
| <b>Parameters for directional light sources:</b>  |       |      |  |                |
| Peak luminous intensity (cd)  |       | -    | Beam angle in degrees, or the range of beam angles that can be set | 95             |
| <b>Parameters for LED and OLED light sources:</b>   |       |      |  |                |
| R9 colour rendering index value   |       | 13   | Survival factor  | -              |
| the lumen maintenance factor  |       | -    |  |                |
| <b>Parameters for LED and OLED mains light sources:</b>   |       |      |  |                |
| displacement factor (cos $\phi_1$ )   |       | 0,95 | Colour consistency in McAdam ellipses                              | -              |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. |       | -(b) | If yes then replacement claim (W)                                  | -              |
| Flicker metric (Pst LM)   |       | -    | Stroboscopic effect metric (SVM)                                   | -              |

(a) '-': not applicable;

(b) '-': not applicable;