

ISSUE 1
PSUL
DESIGN LTD

Serial No. 21080508
Model No. PS50-12-ST
PAC Part No. 7280537

INSP	192	U/BOND	3	TESTED	20	HIPOT	06	BURN	✓	F-ASP	3
MOD LEVEL 0123456789											
3											
GLUED PAS											

MAX OUTPUT POWER : 50W 15.8V @ 3.8A
MAX INPUT CURRENT : 1.4A FUSE RATING: T2A 250 VAC
MAINS INPUT VOLTAGE : 100 - 240VAC 47-63Hz

LED
FLASHING MAINS ONLY
STEADY MAINS & BATTERY

DANGER
DO NOT CONNECT
TO MAINS SUPPLY
UNTIL CORRECTLY
INSTALLED

CE

PRC®
511 DCi
ACCESS CONTROLLER

INPUT: 12-24VDC; 0.18A
(CONTROLLER ONLY)

TCPIP

READER1
+V LED INPUT RTE DC
SIG A (D0) (D1) 0V

READER2
+V LED
SIG B (D0) (D1) 0V

RELAY
LOCK COM NC NO COM

POWER ACCESS
VIN 0V MSTAT LOCK 0V EARTH

ONE TOUCH

LINK TO MANUALS
AND HELP VIDEOS

QR CODE

BARCODE

CE, UKCA, FCC, RoHS, and other regulatory marks.

ISSUE 1
PSU
DESIGN LTD.

Serial No. 21080508
Model No. PS50-12-ST
PAC Part No. 7280537

INSP	E-BOND	TESTED	HIPOT	BURN	FUSE
195	8	20	00	✓	3

MOD LEVEL 0 1 2 3 4 5 6 7 8 9

MAX OUTPUT POWER : 50W 15.8V @ 3.6A
MAX INPUT CURRENT : 1.4A FUSE RATING: T2A 250 VAC
MAINS INPUT VOLTAGE : 100-240VAC 47-63Hz

LED
FLASHING MAINS ONLY
STEADY MAINS & BATTERY

DANGER
DO NOT CONNECT
TO MAINS SUPPLY
UNTIL CORRECTLY
INSTALLED

CE

PRC®
511 DCi
ACCESS CONTROLLER

INPUT: 12-24VDC; 0.18A
(CONTROLLER ONLY)

TCPIP

READER1
+V LED INPUT RTE DC
SIG A (D0) (D1) 0V

RELAY
LOCK COM NC NO COM

READER2
+V LED
SIG B (D0) (D1) 0V

POWER ACCESS
VIN 0V MSTAT LOCK 0V EARTH

ONE TOUCH

LINK TO MANUALS
AND HELP VIDEOS

QR CODE

BARCODE

LED DC RTE DOOR2