

Basic-M4


Recessed mounted luminaire for ceilings, mounting brackets incl - Direct light distribution



Illustrations may only be similar and serve as an orientation.

Basic-M4. LED. Recessed mounted luminaire with surrounding frame for installation in ceilings with cut-out openings. Mounting brackets included. Luminaire body made of high-quality aluminum profile. Surface finish Snow White. Direct only light distribution. Colour temperature: 4000K (Cool White). Colour Rendering Index (CRI): >80. Microprismatic screen for uniform illumination and reduced luminance in office areas. Dimmable DALI. DxH (round). D=670mm. H=100mm.

Low-power current. 4340lm. 28W. 10,2kg. Binning initial \leq MacAdam 3. Protection class: IP20. Protection class I. CE Declaration of Conformity. ENEC-Certification. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,2%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L90B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated



Basic-M4

Recessed mounted luminaire for ceilings, mounting brackets incl - Direct light distribution

Customer / Project: _____

Note: _____



Productname	Basic-M4	Weight (kg)	10,2kg
Lamp	LED		
Installation Type	Recessed mounted luminaire for ceilings, mounting brackets incl		
Surface finish	Snow White		
Light characteristics	Direct light distribution		
Colour temperature	4000K		
Colour Rendering Index (CRI)	CRI>80		
Optical system	Microprismatic screen		
Control	Dimmable (DALI)		
Length L/Diameter D (mm)	D=670mm		
Height H (mm)	H=100mm		
Current/Power	Low-Power		
Luminous Flux	4340lm		
Watt	28W		
Degree of protection	IP20		
Certification	ENEC		
LED lifetime	L90B10 (tq 25°C) = 50.000h		
Photometric code	8 40 / 3 3 9		
Photobiological class	RG0 (EN62471)		
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C		

