

Connector - with TE screw terminals for harsh applications



| Product description | |
|---------------------------|---------------|
| BALS-Prd.-Nr | 3192 |
| EAN | 4024941031929 |
| Product category | TE connector |
| Current | 125A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 9 h |
| Voltage | 380 - 415V~ |

| Product description | |
|------------------------|---|
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing cover grey RAL 7035, Cable gland grey RAL 7035, Collar grey RAL 7035 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 50.0 qmm |
| Cable entry | with cable gland |
| Height | 295mm |
| Width | 125mm |
| Depth | 128mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | For cable diameter from 26 up to max. 50 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 1.13 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941031929 |
| Length | 128 mm |
| Width | 125 mm |
| Height | 295 mm |
| Weight | 1.131 kg |
| Volume | 4,720 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941835398 |
| Length | 345 mm |
| Width | 345 mm |
| Height | 217 mm |
| Weight | 5.985 kg |
| Volume | 24,276 ccm |

