

## Basic-A1

Surface mounted luminaire - Direct light distribution




Illustrations may only be similar and serve as an orientation.



Basic-A1. LED. Surface mounted luminaire for wall or ceiling mounting with minimalist edge. Luminaire body made of high-quality aluminum profile. Surface finish Radiant Silver. Direct only light distribution. Colour temperature: 3000K (Warm White). Colour Rendering Index (CRI): >80. Opal diffuser for enhanced light transmission and perfect uniform illumination. Switchable. DxH (round). D=500mm. H=75mm. Medium-

power current. 4684lm. 35W. 5,7kg. Binning initial <= MacAdam 3. Protection class: IP40. Protection class I. CE Declaration of Conformity. ENEC-Certification. IK02. 220-240V. 50-60 Hz. RG0 (EN62471). Luminous flux reduction up to 0,3%/1.000 operating hours. Nominal failure rate: 0,2%/1.000 operating hours. L85B10 (tq 25°C) = 50.000h. 5 years warranty. Manufacturer: Lightnet GmbH, ISO 9001:2015 certificated



# Basic-A1

Surface mounted luminaire - Direct light distribution

Customer / Project: \_\_\_\_\_

Note: \_\_\_\_\_  
 \_\_\_\_\_



Productname	Basic-A1
Lamp	LED
Installation Type	Surface mounted luminaire
Surface finish	Radiant Silver
Light characteristics	Direct light distribution
Colour temperature	3000K
Colour Rendering Index (CRI)	CRI>80
Optical system	Opal diffuser
Control	Switchable
Length L/Diameter D (mm)	D=500mm
Height H (mm)	H=75mm
Current/Power	Medium-Power
Luminous Flux	4684lm
Watt	35W
Degree of protection	IP40
Certification	ENEC
LED lifetime	L85B10 (tq 25°C) = 50.000h
Photometric code	8 30 / 3 3 9
Photobiological class	RG0 (EN62471)
Indoor/Outdoor	Indoor: ta [ambient] max. 25°C
Weight (kg)	5,7kg

