

Connector - with screw terminals one piece housing



Product description	
BALS-Prd.-Nr	310364
EAN	4024941097444
Product category	TLS connector MULTI-GRIP cable gland
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure red RAL 3000, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	190mm
Width	101.5mm
Depth	106mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical properties	
	one piece housing, MULTI-GRIP cable gland with gasket and integrated strain relief, For cable diameter from 11 up to max. 23,5 mm

Logistics data	
Weight/pcs	0.382 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941097444

Logistics data	
Length	106 mm
Width	101.5 mm
Height	190 mm
Weight	0.383 kg
Volume	2,044.21 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941955034
Length	325 mm
Width	217 mm
Height	210 mm
Weight	4.026 kg
Volume	13,588.4 ccm

