

## Han Vv 20-1 Multiplier



Part number	09 42 020 0111
Specification	Han Vv 20-1 Multiplier
HARTING eCatalogue	<a href="https://b2b.harting.com/09420200111">https://b2b.harting.com/09420200111</a>

### Identification

Category	Inserts
Series	Han D <sup>®</sup> AV
Element	Distributor
Specification	20 termination points

### Version

Termination method	Screw termination
Details	Optionally mountable to terminal block connectors

### Technical characteristics

Conductor cross-section	0.2 ... 2.5 mm <sup>2</sup>
Electrical data acc. to IEC 61984	16 A 400/690 V 6 kV 3
Rated current	16 A
Rated voltage conductor-earth	400 V
Rated voltage conductor-conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL	600 V
Insulation resistance	≥10 <sup>10</sup> Ω
Limiting temperature	-40 ... +125 °C
Tightening torque	0.5 Nm

### Material properties

Material (insert)	Polycarbonate
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Tin plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant



Pushing Performance

## Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

## Specifications and approvals

Specifications	EN 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076

## Commercial data

Packaging size	1
Net weight	89.8 g
Country of origin	Germany
Customs tariff number	85366990