

Connector - with screwless terminals for harsh applications




Product description	
BALS-Prd.-Nr	310492
EAN	4024941192255
Product category	QUICK-CONNECT TE connector
Current	63A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	7 h
Voltage	480 - 500V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	black RAL 9005
Colour of appliance	Collar black RAL 9005, Hinged lid black RAL 9005, Cable gland grey RAL 7035, Housing cover black RAL 9005
Connection design	screwless spring terminal with box terminals and kontext-contact
Maximum conductor size	16,0 qmm
Cable entry	with cable gland
Height	252mm
Width	97mm
Depth	109mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical properties	
	For cable diameter from 16 up to max. 36 mm, Screwless housing connection, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings

Logistics data	
Weight/pcs	0.75 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941192255
Length	109 mm
Width	97 mm
Height	252 mm
Weight	0.751 kg
Volume	2,664.396 ccm
Packaging	Carton
Content amount	5 ST
EAN	4024941834858
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.956 kg
Volume	13,588.4 ccm

	Øa c b 3 MB 107 Ød					
	Ampere Polzahl a Ø b c d Ø Leiter mm² min Leiter mm² max	63 3 95,0 251,0 109,0 36,0 6 16	63 4 95,0 251,0 109,0 36,0 6 16	63 5 95,0 251,0 109,0 36,0 6 16		